


# Single Phase Domestic And Mini Monoblock Installation Procedure

## 1. Prepare A Level Concrete Foundation

---

1. Prepare a level concrete foundation for mounting the Single Phase Self-Priming Monoblock and tighten the motor base using the foundation bolts as shown in Fig. 1 below:



**Fig. 1**  
Assembling Self - Priming Monoblock On A Concrete Foundation


## 2. Use Prescribed Pipe Sizes As Mentioned On The Product Name Plate

---

## 3. Place The Pump Center Line To The Water Surface 3 - 6 Meter Distance Product Name Plate

---

4. Ensure the strainer is fixed to the end of suction pipe located inside the sump/well. Refer Fig. 2, shown below, for recommendations:




**Fig. 2**  
Recommendations For Locating The Self-Priming Pump And Strainer

**5. Use As Few Pipe Fittings As Possible In The Suction Line And Use A Good Quality Foot Valve To Reduce Suction Losses**

---

**6. In Case The Pump Is Used To Draw Water From A Water Line, Follow The Recommended Suction Pipe Orientation Shown In Fig. 3 Below To Minimize The Noise Level**

---



**Fig. 3**  
**Preferred Orientation Of Suction Pipe For Pumping From A Water Line**

**7. Initially Fill The Water In Pump By Removing Filling Plug For Priming. Replace The Filling Plug And Tighten It**

---

## 8. Electrical Installation

---

- Ground the Single Phase Self-Priming Monoblock using the earth screws provided on the leg of the motor body / on the motor body.
- Ensure electrical joints, if any, are properly and adequately insulated.
- Connect the cable to a MCB with appropriate rating.
- Factor in low voltage operation while selecting cable size.

## 9. Power Cable Connection

---

- The motors are internally wired and pre-connected with the capacitor leads with two leads emerging out from the Terminal Box Cover.
- Only Phase and Neutral need to be connected to these two leads (A1 & A2).